

We claim:

1. A template positionable in a main well bore and configured for drilling an offset well bore from the main well bore, said template comprising:

a body having a proximal face and a distal face, said body enclosing a primary chamber;

a tubular inlet leg engaging said proximal face and aligned with an inlet opening in said proximal face;

a tubular main outlet leg engaging said distal face and aligned with a main outlet opening in said distal face; and

a tubular offset outlet leg engaging said distal face and aligned with an offset outlet opening in said distal face, wherein said inlet leg is free from intersection with said main outlet leg or said offset outlet leg within said primary chamber.

2. The template of claim 1 wherein said inlet leg and said main outlet leg are coaxially aligned about a substantially vertical main axis.

3. The template of claim 1 wherein said offset outlet leg is substantially parallel to said inlet leg and said main outlet leg.

4. The template of claim 1 wherein said body is substantially cylindrical.

5. The template of claim 1 wherein said body encloses at least one by-pass tube extending from said proximal face to said distal face in fluid isolation from said primary chamber.

6. The template of claim 1 further comprising a diverter positioned in said body to define a drill string path from said inlet leg to said offset outlet leg.

7. The template of claim 1 further comprising a diverter positioned in said body to define a drill string path from said inlet leg to said main outlet leg.

8. The template of claim 1 further comprising a diverter positioned in said main outlet leg to provide a pressure seal in said main outlet leg and enable pressure stimulation through said offset outlet leg.

9. A template positionable in a main well bore and configured for circulating fluids through the main well bore, said template comprising:

990019 D01

a body;

a tubular inlet leg, a tubular main outlet leg, and a tubular offset outlet leg,
said legs opening into said body;

5 a straddle assembly including a straddle tube having proximal and distal
ends and proximal and distal seals positioned substantially at said proximal and
distal ends, wherein said proximal seal is mounted in said inlet leg and said distal
seal is mounted in said main outlet leg to provide a continuous straddle
assembly flow path through said body substantially preventing fluid flow from
said inlet leg into said offset outlet leg; and

10 a continuous downhole flow path through said inlet leg, said straddle
assembly, and said main outlet leg.

10. The template of claim 9 further comprising an offset plug positioned
in said offset outlet leg.

15 11. The template of claim 9 wherein said body has a proximal face and
a distal face, said body encloses a primary chamber, said tubular inlet leg
engages said proximal face and is aligned with an inlet opening in said proximal
face, said tubular main outlet leg engages said distal face and is aligned with a
main outlet opening in said distal face, and said tubular offset outlet leg engages
said distal face and is aligned with an offset outlet opening in said distal face.

20 12. The template of claim 9 wherein said inlet leg and said main outlet
leg are coaxially aligned about a substantially vertical main axis.

13. The template of claim 9 wherein said offset outlet leg is
substantially parallel to said inlet leg and said main outlet leg.

25 14. The template of claim 9 wherein said body is substantially
cylindrical.

15. The template of claim 9 wherein said body encloses at least one
by-pass tube extending from said proximal face to said distal face in fluid
isolation from said downhole flow path.

30 16. A template positionable in a main well bore and interchangeably
configured for circulating fluids through the main well bore or for drilling an offset
well bore from the main well bore, said template comprising:

a fluid circulation configuration having a body, a tubular inlet leg, a tubular main outlet leg, a tubular offset outlet leg, said legs opening into said body, a straddle assembly including a straddle tube having proximal and distal ends and proximal and distal seals positioned substantially at said proximal and distal ends, wherein said proximal seal is mounted in said inlet leg and said distal seal is mounted in said main outlet leg to provide a continuous straddle assembly flow path through said body substantially preventing fluid flow from said inlet leg into said offset outlet leg, and a continuous downhole flow path through said inlet leg, said straddle assembly, and said main outlet leg; and

an offset well bore drilling configuration having said body, said inlet leg, said main outlet leg, and said offset outlet leg, wherein said straddle assembly is removed from said body to provide a drill string path from said inlet leg to said offset outlet leg or said main outlet leg.

17. The template of claim 16 wherein said inlet leg and said main outlet leg are coaxially aligned about a substantially vertical main axis in said fluid circulation and offset well bore drilling configurations.

18. The template of claim 16 wherein said offset outlet leg is substantially parallel to said inlet leg and said main outlet leg in said fluid circulation and offset well bore drilling configurations.

19. The template of claim 16 wherein said body is substantially cylindrical in said fluid circulation and offset well bore drilling configurations.

20. The template of claim 16 further comprising an offset plug positioned in said offset outlet leg in said fluid circulation configuration.

21. A template system having a plurality of templates, the system configured for circulating a fluid in a well bore, the system comprising:

an initial template and a first additional template, each said initial and first additional templates including,

a body, a tubular inlet leg, a tubular main outlet leg and a tubular offset outlet leg, said legs opening into said body,

a straddle assembly including a straddle tube having proximal and distal ends and proximal and distal seals positioned substantially at said

proximal and distal ends, wherein said proximal seal is mounted in said inlet leg and said distal seal is mounted in said main outlet leg to provide a continuous straddle assembly flow path through said body substantially preventing fluid flow from said inlet leg into said offset outlet leg, and
5 a continuous downhole flow path through said inlet leg, said straddle assembly, and said main outlet leg,
wherein said main outlet leg of said initial template is serially connected to said inlet leg of said first additional template to connect said continuous downhole flow path of said initial template to said continuous downhole flow path of said
10 first additional template.

22. The template system of claim 21 further comprising;
second or more additional templates, each said second or more additional templates including said body, said inlet leg, said main outlet leg, said offset outlet leg, and said straddle assembly, wherein said second or more additional
15 templates are positioned in series, and wherein said main outlet leg of said first additional template is serially connected to said inlet leg of said second additional template and said main outlet leg of said second additional template is serially connected to said inlet leg of said next additional template to interconnect said continuous downhole flow paths of said templates.

20 23. A template system positionable in a main well bore and having a plurality of templates, the system configured for drilling at least one offset well bore through one of the templates from the main well bore, the system comprising:

an initial template and a first additional template, each said initial and first
25 additional templates including,

a body having a proximal face and a distal face, said body enclosing a primary chamber,

a tubular inlet leg engaging said proximal face and aligned with an inlet opening in said proximal face,

30 a tubular main outlet leg engaging said distal face and aligned with a main outlet opening in said distal face, and

990019 D01

a tubular offset outlet leg engaging said distal face and aligned with an offset outlet opening in said distal face, wherein said inlet leg is free from intersection with said main outlet leg or said offset outlet leg within said primary chamber,

5 wherein said main outlet leg of said initial template is serially connected to said inlet leg of said first additional template.

24. The template system of claim 23 further comprising;

second or more additional templates, each said second or more additional templates including said body, said inlet leg, said main outlet leg, and said offset
10 outlet leg, wherein said main outlet leg of said first additional template is serially connected to said inlet leg of said second additional template and said main outlet leg of said second additional template is serially connected to said inlet leg of said next additional template.